

tesa® 60950 Anti Slip safety solution

The application area for tesa® Anti Slip Professional range is everywhere safe footing is required. Anti Slip black is the ideal protection to prevent from skidding and therefore helps to avoid accidents in the job related. Very good adhesion of the product is suitable for demanding surfaces such as factory floors, industry areas etc. The strong and durable adhesive coating secures a high Anti Slip effect of up to 1- 2 years in normal use areas. The Anti Slip tapes are hand tearable and no shrinkage occurs after application.

Main Application

Everywhere safe footing is required.

Technical Data

▪ Backing material	PVC film	▪ Adhesion to steel	5.8 N/cm
▪ Total thickness	800 µm	▪ Elongation at break	25 %
▪ Type of adhesive	acrylic	▪ Temperature resistance	-5 to +50 °C

Properties

▪ Hand tearability	●●●	▪ Resistance to chemicals	●●●
▪ Suitable for die cutting	yes	▪ Salt water resistant	●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=60950>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.