

tesa® 61795

200µm double sided black high performance filmic tape

tesa® 61795 is a double sided self-adhesive tape consisting of a black PET backing and a tackified acrylic adhesive.

Special features:

- Thickness: 200µm
- High bonding strength
- High push out resistance
- Superior shock resistance
- Excellent resistance to demanding environmental conditions
- Black colour

Main Application

- Lens mounting in mobile phones
- Touch panel mounting

Technical Data

▪ Backing material	PET film	▪ Tensile strength	20 N/cm
▪ Color	black	▪ Type of liner	glassine
▪ Total thickness	200 µm	▪ Colour of liner	white with tesa logo
▪ Type of adhesive	tackified acrylic	▪ Thickness of liner	71 µm
▪ Elongation at break	50 %		

Adhesion to

▪ Steel (initial)	11.2 N/cm	▪ Steel (after 14 days)	12.5 N/cm
▪ ABS (initial)	9.6 N/cm	▪ ABS (after 14 days)	12.3 N/cm
▪ Aluminium (initial)	9.9 N/cm	▪ Aluminium (after 14 days)	10.7 N/cm
▪ Glass (initial)	13.1 N/cm	▪ Glass (after 14 days)	13.3 N/cm
▪ PC (initial)	12.2 N/cm	▪ PC (after 14 days)	16.0 N/cm
▪ PE (initial)	5.2 N/cm	▪ PE (after 14 days)	5.6 N/cm
▪ PMMA (initial)	13.8 N/cm	▪ PMMA (after 14 days)	15.1 N/cm

Properties

▪ Temperature resistance short term	200 °C	▪ Softener resistance	●●●●
▪ Temperature resistance long term	100 °C	▪ Static shear resistance at 23°C	●●●●
▪ Tack	●●	▪ Static shear resistance at 40°C	●●●●
▪ Humidity resistance	●●●●		

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=61795>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.