

## tesa® 62010 Card Labels

tesa® 62010 is a double-sided adhesive label for the automatic or manual fixing of cards to paper. The open side of the label is made of a reversible adhesive which is optimised for the temporary attachment to all card materials. The reverse side of the label, which lies on the release liner, consists of a permanent adhesive that enables a secure and reliable fixing to paper. After the mailing process the card can be removed easily without leaving behind any residues or stains. Therefore tesa® 62010 is an optimised solution for the mailing of all card types.

### Features:

- Easily removable without leaving residues or damaging the card
- High adhesive reliability to all card surfaces and materials
- High processing reliability
- UV pigments enable the sensory label detection
- Up to 10,000 labels/hr can be applied automatically

## Main Application

Mailing of cards

## Technical Data

- |                    |                               |                                      |          |
|--------------------|-------------------------------|--------------------------------------|----------|
| ▪ Backing material | PET                           | ▪ Adhesion to Steel (permanent side) | 4 N/cm   |
| ▪ Color            | transparent with UV-particles | ▪ Adhesion to Steel (removable side) | 0.3 N/cm |
| ▪ Total thickness  | 120 µm                        | ▪ Type of liner                      | glassine |
| ▪ Type of adhesive | modified acrylic              |                                      |          |

## Properties

- |                        |     |
|------------------------|-----|
| ▪ Residue free removal | yes |
|------------------------|-----|

## Additional Information

Standard Version:  
Label Format: 38mm x 17mm  
Labels/roll: 5000 pcs.

For latest information on this product please visit <http://l.tesa.com/?ip=62010>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.