

tesa® 62708

Double-sided PE foam tape

tesa® 62708 is a double-sided tape consisting of a PE foam backing and a pure acrylic adhesive.

tesa® 62708 features especially:

- Excellent temperature resistance performance
- High ultimate adhesive strength for a secure bonding performance
- Conformable foam backing to compensate design tolerances or uneven surfaces
- Excellent converting properties

Main Application

Permanent mounting of emblems and letters; e.g. single letters for classification of car model or engine data.

Technical Data

▪ Backing material	PE foam	▪ Type of adhesive	pure acrylic
▪ Color	black	▪ Elongation at break	440 %
▪ Total thickness (mm)	0.8 mm	▪ Tensile strength	18 N/cm

Adhesion to

▪ Steel (initial)	8.0 N/cm	▪ Steel (after 14 days)	15.0 N/cm
▪ ABS (initial)	5.0 N/cm	▪ ABS (after 14 days)	15.0 N/cm

Properties

▪ Temperature resistance short term	120 °C	▪ Static shear resistance at 40°C	●●●●
▪ Temperature resistance long term	100 °C	▪ Static shear resistance at 70°C	●●●●
▪ Static shear resistance at 23°C	●●●●		

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

Additional Information

Liner variants:

PV0: brown glasine paper (71µm)

PV6: red MOPP film (80µm)

For latest information on this product please visit <http://l.tesa.com/?ip=62708>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.