# productinformation

# tesa® 64014

## Low noise water based acrylic carton sealing tape

tesa<sup>®</sup> 64014 is based on a PP-backing coated with a water based acrylic adhesive. The special material combination guarantees a low noise unwinding behaviour. Due to the characteristics of the water based acrylic adhesive tesa<sup>®</sup> 64014 has a high age and light resistance. As the product is chlorine free and based on derivatives of mineral oil only, the disposal by heat treatment is environmental friendly.

#### Main Application

Manual sealing of light and medium-range weight cartons.

Technical Data			
<ul><li>Backing material</li><li>Total thickness</li><li>Type of adhesive</li></ul>	PP film 45 μm acrylic	<ul><li>Adhesion to steel</li><li>Elongation at break</li><li>Tensile strength</li></ul>	2.4 N/cm 140 % 35 N/cm
Properties			
<ul> <li>Manual application</li> </ul>	yes	<ul> <li>Low noise unwinding</li> </ul>	yes

### Additional Information

tesa<sup>®</sup> 64014 can be applied on all manual dispenser. For a more convenient application it is recommended to loose the dispenser friction. The PV1-version of the product is printable. Available colours: white, havana and transparent

For latest information on this product please visit <a href="http://l.tesa.com/?ip=64014">http://l.tesa.com/?ip=64014</a>

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

