



# tesa<sup>®</sup> Ultra Power Extreme repair tape

## Product Information

BNR 56622, 56623

### Product Description

For some tasks, an average repairing tape is simply not strong enough. Do not let small emergencies ruin your big adventures. tesa<sup>®</sup> Ultra Power Extreme Repairing Tape provides the needed extra strength. It is a versatile tape with extremely strong adhesion that can be used on many surfaces, smooth or rough. It is made for a variety of tasks such as patching holes, cracks, gaps, tears, and fixing broken parts. With its high UV- and temperature-resistance, it is suitable even for extreme weather.

### Product Features

- Powerful adhesion: Extremely strong hold for reliable fixing solutions in various challenging environments
- High Versatility: Thanks to its strong adhesive, the tape sticks perfectly even on rough surfaces
- Designed to last: Extra-durable due to its high abrasion resistance
- Extremely weather-resistant, waterproof, and UV-resistant for demanding outdoor tasks
- High-quality tool: The cloth-laminated backing makes this duct tape even stronger
- Easy to use: Highly convenient thanks to a simple hand-tearability
- Multi-purpose repairing tape: Can be used both indoors and outdoors
- Convenient solution for fast emergency fixes: Ideal for repairing broken parts, can be used e.g. to repair small damages on bumpers
- Fix your damages fast and reliably: Suitable for patching holes, cracks, gaps, and tears

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                |                   |        |
|--------------------|----------------|-------------------|--------|
| • Backing          | PET cloth      | • Total thickness | 420 µm |
| • Type of adhesive | natural rubber |                   |        |



# tesa<sup>®</sup> Ultra Power Extreme repair tape

## Product Information

### Properties/Performance Values

• Tensile strength	60 N/cm	• Oil and grease resistance	yes
• Abrasion resistance	yes	• Ozone resistance	yes
• Adhesive strength	Very high adhesion	• Residue-free removability	no
• Ageing resistance (UV)	yes	• Solvent free	yes
• Applicationfield	Car, Home, Garden, Garage	• Suitable surfaces	Most plastics, Steel, Glass, Metal
• Area of use	In- and Outdoor	• Tear resistance	yes
• Batteries included	no	• Temperature resistance	yes
• Batteries required	no	• Temperature resistance max.	90 °C
• Ecofriendly packaging	no	• Temperature resistance min.	-15 °C
• Hand tearability	yes	• UV resistant	yes
• Hazard material	no	• Waterproof	yes
• Material	PE (polyethylene)	• Writable	no

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>