



tesa[®] Fiberglass tape

Product Information

BNR 52512

Product Description

tesa[®] Fiberglass Tape is a superior product for a wide range of applications. Thanks to its material and great adhesive properties, the product guarantees effective results. This multi-purpose tape is highly versatile and is suitable to use even on rough surfaces - a smart solution for patching drywalls and covering gaps.

Carefully designed to last thanks to its very good tear-resistant and self-adhesive properties. Achieve excellent looks and high-quality results with tesa[®] Fiberglass Tape.

Product Features

- Highly tear-proof self-adhesive fiberglass tape
- For high-quality and smooth repairs on various surfaces
- Durable design made to last: Resistant and perfect for drywall repair
- Ideal multi-use repair tape for patching drywall and covering gaps in walls
- Easy to use and hassle-free: Sticks quickly and easily on any clean, dry and dust-free surface
- Achieve high-quality results with seamless transitions between wall and ceiling

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------|-------------------|--------|
| • Backing | fibreglass | • Total thickness | 185 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|----------------------|---------|----------------------|----|
| • Tensile strength | 50 N/cm | • Batteries required | no |
| • Batteries included | no | | |



tesa[®] Fiberglass tape

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>