




# tesa® 66530

## Product Information



tesa® 66530 40µm single sided high temperature resistant removable PI tape

### Product Description

tesa® 66530 is a single-sided self-adhesive tape consisting of an amber PI film with special high temperature resistant removable acrylic adhesive.

#### Special features:

- Excellent removability on various substrates after high temperature processing
- Temperature resistance up to 260°C
- Excellent resistance to demanding environmental conditions
- Very good handling performance in converting processes

### Application Fields

- Removable mounting
- Temporary fixation under high temperature & high humidity processing and operating environments

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |           |                   |             |
|--------------------|-----------|-------------------|-------------|
| • Backing          | Polyimide | • Total thickness | 40 µm       |
| • Type of adhesive | acrylic   | • Color           | amber       |
| • Type of liner    | PET film  | • Color of liner  | transparent |

### Adhesion to Values

- |                         |           |                         |           |
|-------------------------|-----------|-------------------------|-----------|
| • Glass (initial)       | 0.27 N/cm | • Steel (initial)       | 0.24 N/cm |
| • Glass (after 14 days) | 0.36 N/cm | • Steel (after 14 days) | 0.42 N/cm |



# tesa<sup>®</sup> 66530

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=66530>