



51458

LabelLine Premium

Product Information

Double-sided splicing tape

Product Description

tesa® 51458 EasySplice® LabelLine Premium is a double-sided integrated flying splice tape consisting of a flat-back paper and a modified acrylic adhesive

Color: Blue

Product Features

- Very high tack properties
- Very high shear resistance on paper substrates
- Very good adhesion values on coated and uncoated paper
- Low splice thickness
- Printable and coatable backing
- Slit liner for the secure fixation of the top sheet
- Adhesive formulation with very high tack properties for excellent contact between expiring web and new reel
- Two splitting strips with paper backing for a smooth opening of the new paper reel without jeopardizing the coating process and for a secure attachment of the tape to the paper roll - no folding back fo tape while attaching top sheet

Application Fields

tesa® 51458 EasySplice® LabelLine Premium is particularly suitable for:

- Flying splices of paper faces and backings in the label stock industry at splicing speeds <600m/min.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------------|-------------------|--------|
| • Backing | Paper | • Total thickness | 100 µm |
| • Type of adhesive | tackified acrylic | • Color | blue |
| • Type of liner | bi-siliconised paper | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-----------------------------------|-----------|
| • Elongation at break | 6 % | • Shelf life time (packed) < 25°C | 12 months |
| • Tensile strength | 30 N/cm | | |



51458

LabelLine Premium

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51458>