




tesa® 54994

製品案内



耐チッピング用保護フィルム

製品の説明

tesa® 54994は、透明性が高く厚いPUフィルム基材に強粘着のアクリル系粘着剤を片面に塗布した製品です。

特徴

- Highly transparent product design
- Perfect optical clarity makes the film virtually invisible when applied to painted surfaces
- Resistant and durable against mechanical and environmental forces
- Additional topcoat provides outstanding gloss and enhances its exterior durability
- long-term UV resistance and self-healing properties without turning yellow over the vehicle's lifetime
- Good conformability makes it ideal for curves and complex surface geometries
- Dimension stability and die-cuttablity
- Compatible with several paint and clearcoat systems
- customized die-cut solutions with visual positioning features help the workers to determine the exact position

用途

tesa® 54994は、路面などから跳ね上がる小石などが自動車のボディに傷をつけてしまう所謂チッピング対策専用開発された表面保護フィルムです。摩耗や擦り傷からの塗面保護、耐衝撃対策などにご利用ください。

仕様 (代表値)

下記に記載の数値は実測値の代表値であり、保証値ではございません。

製品の構成

• 基材	PUフィルム	• 総厚	260 µm
• 粘着剤	アクリル系	• 色	透明
• ライナー	PETフィルム		

特性 / 性能

• 破断伸び	340 %	• 耐薬品性	非常に優れる
• 耐熱性 (30分)	90 °C		

備考

tesa® 54994は、お客様の仕様及び用途によって、ロールあるいはシート単位での納品になります。

標準製品の厚み

最新の情報は下記リンク先をご参照ください。 <http://l.tesa.com/?ip=54994>



tesa® 54994

製品案内

備考

54994 PV0 : 260µm

54994 PV3 : 360µm

免責事項

tesa® (テサ®) 製品は自社の規定に基づき定期的に品質の検査をおこなっています。本書に記載されている情報はすべて様々な分野での知見や実経験に基づいて提示している代表値であり、保証値ではございません。便宜上、製品の適格性や用途に関する記述がございますが、いかなる場合も特定の用途に関する保証や明示、黙示等は致しかねます。お客様の環境によって問題が生じる場合がございますため、お客様のご判断のもとご使用いただくようお願い申し上げます。ご質問等ございましたら、弊社(テサテープ株式会社)へお問い合わせください。



最新の情報は下記リンク先をご参照ください。 <http://l.tesa.com/?ip=54994>