




# tesa® 54994

## 製品案内



## Parmanent Paint Protection Die-Cuts

### 製品の説明

tesa® 54994 are customized die-cut solutions based on material of tesa® 52994

tesa® 52994 is a single sided transparent protection film with a clear gloss aliphatic polyurethan backing, a permanent acrylic adhesive and a polyester liner.

We are specialized in customizing the shapes and sizes of our products according to individual specifications and customer preferences.

### 特徴

- Highly transparent product design
- Perfect optical clarity makes the film virtually invisible when applied to painted surfaces
- Resistant and durable against mechanical and environmental forces
- Additional topcoat provides outstanding gloss and enhances its exterior durability
- long-term UV resistance and self-healing properties without turning yellow over the vehicle's lifetime
- Good conformability makes it ideal for curves and complex surface geometries
- Dimension stability and die-cuttability
- Compatible with several paint and clearcoat systems
- customized die-cut solutions with visual positioning features help the workers to determine the exact position

### 用途

Depending on the car design, there are certain areas that are highly vulnerable to mechanical damage, scratches and corrosion. tesa® 54994 Permanent Paint Protection Films can be applied to protect these high impact areas of the vehicle without changing its design features.

tesa® 54994 is applied to permanently protect sensitive surfaces against strong mechanical forces in interior and exterior applications. It is specially designed for permanent paint protection against stone chipping, abrasion, scratches and corrosion in automotive applications e.g.

- wheel arches
- door edges
- side skirts
- door sill trims
- trunk edges
- front and rear bumpers
- VIN labels
- ...

Due to its good conformability, it can be applied to even and slightly curved surfaces.

最新の情報は下記リンク先をご参照ください。 <http://l.tesa.com/?ip=54994>



# tesa® 54994

## 製品案内

### 仕様 ( 代表値 )

下記に記載の数値は実測値の代表値であり、保証値ではございません。

### 製品の構成

• Backing material Grid	PUフィルム	• 総厚	260 µm
• Type of adhesive Grid	アクリル系	• 色	透明, 光学透明
• Type of liner Grid	PETフィルム		

### 特性 / 性能

• 破断伸び	340 %	• 耐薬品性	非常に優れる
• 耐熱性 ( 30分 )	90 °C		

### 備考

tesa® 54994 is available in different thicknesses

- tesa® 54994 PV5 - 187 µm
- tesa® 54994 PV0 - 260 µm
- tesa® 54994 PV3 - 360 µm

For more details, please refer to product information of tesa® 52994 PV0, PV3 and PV5.

### 免責事項

tesa® ( テサ® ) 製品は自社の規定に基づき定期的に品質の検査をおこなっています。本書に記載されている情報はすべて様々な分野での知見や実経験に基づいて提示している代表値であり、保証値ではございません。便宜上、製品の適格性や用途に関する記述がございますが、いかなる場合も特定の用途に関する保証や明示、黙示等は致しかねます。お客様の環境によって問題が生じる場合がございますため、お客様のご判断のもとご使用いただくようお願い申し上げます。ご質問等がございましたら、弊社 ( テサテープ株式会社 ) へお問い合わせください。



最新の情報は下記リンク先をご参照ください。 <http://l.tesa.com/?ip=54994>