

tesa® 4378 Easy Cover® Auto

제품 정보

3-in-1 / Car body masking solution for large areas

제품 설명

tesa[®] 4378 Easy Cover[®] Auto is a 3-in-1 system for masking large areas for car body repair. The convenient system is comprised of the slightly crepe paper masking tape tesa[®] 4309 with natural rubber adhesive, a masking paper border and HDPE masking film, working together to ensure optimal protection. tesa[®] 4309 is a conformable and flexible paper masking tape. It is suitable for spray-painting applications, with subsequent oven-drying up to a temperature of 120°C.

특성

- · Ideal for masking large areas easily and quickly
- Temperature resistance up to 120°C
- · Additional masking paper border providing excellent paint absorption
- · Reduction of logistic complexity
- tesa® 4378 Easy Cover® Auto allows a single person to cover large areas easily and quickly as well as reducing the logistic complexity.
- It is specifically treated for better paint adherence and clings to the car body.
- The additional masking paper border provides excellent paint absorption at the most critical area close to the repair spot.
- The HDPE film serves for the protection against spray particles.

Applications

- tesa® 4378 Easy Cover® Auto is recommended for professional masking during spray painting work for industrial applications and car body repair
- The 3-in-1 system is ideal for masking large areas easily and quickly for the protection against spray particles
- tesa® 4378 Easy Cover® Auto can withstand temperatures of up to 120°C

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

제품 구조

• 기재 소재	약간 크레이프화된	• 총두께	170 μm
	조이		

• 점착제 종류 천연고무

속성 / 성능 값

•	연신률	12 %	•	마스킹 커버 두께	10 μm
•	인장강도	47 N/cm	•	마스킹 커버 재료	HDPE
•	떼어내기 쉬운	네	•	추가보호용지 중량	37 g/m ²



tesa® 4378 Easy Cover® Auto

제품 정보

점착력(수치)

• Steel점착력

3.5 N/cm

공지사항

테사에서 판매하는 제품들은 엄격한 품질관리를 통해 생산되고 있으며, 테사에서 제공하는 전문적인 정보들은 오랜기간의 경험을 기반으로 하고

있습니다. 관련 정보는 평균값에 근거하며, 특별한 용도에는 적합하지 않을 수 있습니다. tesa SE는 관련 정보의 명시적 또는 암묵적인 보증을 하는 것은 아니며, 이는 특별한 용도에 적합성

또는 상업성과 관련한 어떠한 암묵적인 보증도 포함하지 않습니다. 사용자는 제품을 사용하기 전에 적용부위에 적합한지를 검토하시기 바라며, 기타 문의사항이 있으시면 저희 직원에게 문의 바랍니다

