



tesa® 60687

제품 정보

700µm single sided gray electrically conductive foam tape

제품 설명

tesa® 60687 is a gray single sided electrically conductive self adhesive foam tape. It consists of a highly compressible electrically conductive foam backing and an electrically conductive adhesive.

특성

- Highly compressible with very low force
- Excellent recovery property
- Excellent conformability to surface variations and tolerances
- Good electrical conductivity over a wide working range in XYZ-direction even at high temperatures and humidity
- High bonding strength even at harsh environmental conditions
- Excellent shock absorbing and cushioning properties

Applications

- Conductive gap filling
- EMI shielding and grounding applications
- Electrostatic discharge applications

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

제품 구조

- | | | | |
|----------|-----------|----------|-----------|
| • 기재 소재 | 전도성 품 | • 컬러 | 회색 |
| • 점착제 종류 | 전도성 아크릴 | • 이형지 두께 | 120 µm |
| • 이형지 종류 | PE 코팅된 직물 | • 이형지 색깔 | 흰색/파란색 로고 |
| • 총두께 | 700 µm | | |

속성 / 성능 값

- | | | | |
|--------------------|---------------------------|------------------|------------------|
| • z-축 방향 접촉저항 (초기) | 0.03 Ohm / square
inch | • 이형지 제거 | 간단함 |
| • 단기간 온도저항 | 200 °C | • 표면 저항 x-y-축 방향 | 0.2 Ohm / square |

점착력

- | | |
|----------------------|--------|
| • Steel 점착력 (14일 경과) | 8 N/cm |
|----------------------|--------|



tesa® 60687

제품 정보

비고

700μm single sided gray electrically conductive foam tape

면책사항

테사에서 판매하는 제품들은 엄격한 품질관리를 통해 생산되고 있으며, 테사에서 제공하는 전문적인 정보들은 오랜기간의 경험을 기반으로 하고 있습니다. 관련 정보는 평균값에 근거하며, 특별한 용도에는 적합하지 않을 수 있습니다. tesa SE는 관련 정보의 명시적 또는 암묵적인 보증을 하는 것은 아니며, 이는 특별한 용도에 적합성 또는 상업성과 관련한 어떠한 암묵적인 보증도 포함하지 않습니다. 사용자는 제품을 사용하기 전에 적용부위에 적합한지를 검토하시기 바라며, 기타 문의사항이 있으시면 저희 직원에게 문의 바랍니다.

최신정보는 왼쪽 링크를 클릭하세요. <http://l.tesa.com/?ip=60687>