


tesa® 7905

제품정보



5 µm single sided matte black filmic tape

제품 설명

tesa® 7905 is a matte black single sided tape consisting of an ultra-thin PET film backing and tackified acrylic adhesive

특성

- Thickness: 5µm
- Strong reliable bonding force
- Refined matte black color tone
- Low gloss level of 2.9 %
- Excellent anti-fingerprint performance
- Excellent solvent-resistance
- Good light blocking

Applications

- Graphite sheet protection
- Magnetic sheet protection
- Ultrathin covering on various components in smartphone and tablet

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

제품 구조

• 기재 소재	PET 필름	• 총 두께	5 µm
• 점착제 종류	아크릴	• 이형지 두께	50 µm
• 이형지 종류	PET		

속성 / 성능 값

• 연신률	10 %	• 단기간 온도저항	140 °C
• 인장강도	4 N/cm	• 절연파괴전압	700 V
• 광학 밀도	1.2		

점착력

• ASTM 점착력 (초기)	0.9 N/cm	• 유리 점착력 (14일 경과)	1 N/cm
• ASTM 점착력 (14일 경과)	1 N/cm	• PC 점착력 (초기)	0.9 N/cm
• 유리 점착력 (초기)	1 N/cm	• PC 점착력 (14일 경과)	1.4 N/cm

tesa[®] 7905

제품정보

면책사항

테사에서 판매하는 제품들은 엄격한 품질관리를 통해 생산되고 있으며, 테사에서 제공하는 전문적인 정보들은 오랜기간의 경험을 기반으로 하고 있습니다. 관련 정보는 평균값에 근거하며, 특별한 용도에는 적합하지 않을 수 있습니다. tesa SE는 관련 정보의 명시적 또는 암묵적인 보증을 하는 것은 아니며, 이는 특별한 용도에 적합성 또는 상업성과 관련한 어떠한 암묵적인 보증도 포함하지 않습니다. 사용자는 제품을 사용하기 전에 적용부위에 적합한지를 검토하시기 바라며, 기타 문의사항이 있으시면 저희 직원에게 문의 바랍니다



최신정보는 왼쪽 링크를 클릭하세요. <http://l.tesa.com/?ip=7905>