




tesa® 77815 Primerless Line



제품 정보

1.5 mm double-sided acrylic foam tape for mounting of automotive exterior attachment parts

제품 설명

tesa® ACX^{plus} 77815 is a double-sided acrylic foam tape for mounting of automotive exterior attachment parts. It is a triple-layer symmetrically designed product, coated on both sides with LSE adhesive. It can help eliminate the primer in the process. Its high-performance LSE adhesive creates an efficient and secure bond to typical automotive attachment parts made of LSE (like PP and PP/EPDM) and MSE (like ABS) plastics without primer.

In addition, our product also has excellent adhesive properties when it comes to different types of OEM clear coats. Thanks to its viscoelastic acrylic foam core, tesa® ACX^{plus} 77815 Primerless Line has the ability to absorb and dissipate dynamic and static loads.

Also available in 0.5mm, 0.8 mm and 1.1 mm formats.

Main Features

- High initial performance on LSE plastics and difficult-to-bond clear coats without primer
- Superior peel-adhesion level right after application
- Excellent bonding stability at an application temperature as low as 5°C
- PFAS / PFOS free Product
- Efficient and robust application
- Viscoelastic acrylic foam core to compensate for different thermal elongation of bonded parts
- Outstanding wet-out property
- High humidity and UV resistance

LSE: low surface energy, MSE: medium surface energy

Applications

tesa® ACX^{plus} 77815 Primerless Line is suitable for a wide range of permanent exterior mounting applications. To ensure the highest performance possible, our aim is to fully understand your application (including the substrates involved) in order to provide the right product recommendation.

Example applications are:

- * Body side moldings and decorative trims
- * Emblems
- * Spoilers
- * Antennas
- * Pillar appliques

최신정보는 왼쪽 링크를 클릭하세요. <http://l.tesa.com/?ip=77815>



tesa[®] 77815 Primerless Line

제품 정보

Applications

* PDC mounting

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

제품 구조

• 기재 소재	Acrylic foam	• 총두께	1500 µm
• 점착제 종류	LSE	• 컬러	회색
• 이형지 종류	PE	• 이형지 색깔	파랑

속성 / 성능 값

• L-지그	good	• 내열 범위	-40 to +80 °C
• T-block	very good	• 노후성 (UV)	good
• 내습성	very good	• 정적 전단응력 (90°C)	very good

점착력

• ABS점착력 (3일 경과)	34 N/cm	• Steel점착력 (14일 경과)	39 N/cm
• ABS점착력 (초기, 1 min)	32 N/cm	• Steel점착력 (3일 경과)	39 N/cm
• PP점착력 (3일 경과)	44 N/cm	• Steel점착력 (초기, 1 min)	36 N/cm
• PP점착력 (초기, 1 min)	34 N/cm		

면책사항

테사에서 판매하는 제품들은 엄격한 품질관리를 통해 생산되고 있으며, 테사에서 제공하는 전문적인 정보들은 오랜기간의 경험을 기반으로 하고 있습니다. 관련 정보는 평균값에 근거하며, 특별한 용도에는 적합하지 않을 수 있습니다. tesa SE는 관련 정보의 명시적 또는 암묵적인 보증을 하는 것은 아니며, 이는 특별한 용도에 적합성 또는 상업성과 관련한 어떠한 암묵적인 보증도 포함하지 않습니다. 사용자는 제품을 사용하기 전에 적용부위에 적합한지를 검토하시기 바라며, 기타 문의사항이 있으시면 저희 직원에게 문의 바랍니다



최신정보는 왼쪽 링크를 클릭하세요. <http://l.tesa.com/?ip=77815>