tesa® 67008 New Bond



제품정보

800µm double-sided acrylic foam tape

제품 설명

tesa® 67008은 회색의 양면 아크릴 폼 테이프이며, AC 폼은 기재 및 접착제로 모두 사용할 수 있습니다.

특성

- Good bonding on various substrates
- Good temperature resistance and aging performance
- Cost-effective as entry level standard product

Applications

Example mounting applications include but are not limited to:

- Decorative glass panel mounting
- Plastic panel mounting
- Nameplate and parts mounting
- TV back panel mounting

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

제품 구조

• 기재 소재	Acrylic foam	• 이형지 종류	PE
• 점착제 종류	변성 아크릴	• 총두께	800 µm
• 이형지 종류	PE 코팅된 직물	• 컬러	회색

제품군

• 가능한 이형지	PE, PE 코팅된 직물

속성 / 성능 값

• 단기간 온도저항	200 °C	• 정적 전단응력 (23°C)	very good
• 장기간 온도저항	100 °C	• 정적 전단응력 (40°C)	very good

점착력

• ABS점착력 (초기)	11 N/cm	• 유리점착력 (초기)	18 N/cm
• ABS점착력 (3일 경과)	13 N/cm	• 유리점착력 (3일 경과)	23 N/cm
• 알루미늄점착력 (초기)	18 N/cm	• Steel점착력 (초기)	17 N/cm
• 알루미늄점착력 (3일 경과)	28 N/cm	• Steel점착력 (3일 경과)	27 N/cm

최신정보는 왼쪽 링크를 클릭하세요. http://l.tesa.com/?ip=67008

tesa® 67008
New Bond

제품정보

면책사항

테사에서 판매하는 제품들은 엄격한 품질관리를 통해 생산되고 있으며, 테사에서 제공하는 전문적인 정보들은 오랜기간의 경험을 기반으로 하고 있습니다. 관련 정보는 평균값에 근거하며, 특별한 용도에는 적합하지 않을 수 있습니다. tesa SE는 관련 정보의 명시적 또는 암묵적인 보증을 하는 것은 아니며, 이는 특별한 용도에 적합성 또는 상업성과 관련한 어떠한 암묵적인 보증도 포함하지 않습니다. 사용자는 제품을 사용하기 전에 적용부위에 적합한지를 검토하시기 바라며, 기타 문의사항이 있으시면 저희 직원에게 문의 바랍니다

최신정보는 왼쪽 링크를 클릭하세요. http://l.tesa.com/?ip=67008