



tesa[®] Mounting Tape for Transparent & Glass 20 kg/m



Product Information

BNR 77741, 77740

Product Description

Mounting Tape for Transparent & Glass holds up to 20kg/m. An almost invisible, permanent solution for mounting objects on transparent and solid surfaces.

Product Features

- For transparent and solid surfaces indoors
- Holds up to 20kg/m
- For permanent applications
- Almost invisible
- For optimal results a max. of 6kg per application/objects is recommended

Application Fields

How to apply – Step by step1. To ensure the best possible bond, the object and the surface must be free of dust, dirt and grease. To clean them, use a brush or a lint-free cloth and a silicone-free cleaner like methylated spirits. Make sure the surface is dry before application.

2. Check if the surface or the object is rougher and apply the mounting tape to the rougher surface.
3. Apply the tape in vertical strips along the full length of the object or surface. Reinforce the upper portion with shorter strips, since that's where most of the load will be born.
4. Press down firmly across the entire surface of Mounting Tape for at least five seconds. Remove the protective film, taking care not to touch the exposed adhesive surface as this could affect the adhesion.
5. Fix the object and press it again at least five seconds.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------------------|---------|
| • Type of adhesive | synthetic rubber | • Holding power of tape up to | 20 KG/M |
| • Total thickness | 500 µm | | |



tesa[®] Mounting Tape for Transparent & Glass 20 kg/m

Product Information

Properties/Performance Values

• Application temperature from	-10 °C	• Residue-free removability	no
• Area of use	Indoor	• Reusable	no
• Batteries included	no	• Reusable with	_NULL
• Batteries required	no	• Solvent free	yes
• Chemical Resistance	no	• Suitable surfaces	Even wood, Tiles, Most plastics, Glass, Acrylic glass, Steel, Metal
• Hazard material	no		
• Humidity resistance	no	• Temperature resistance max.	40 °C
• Material	_NULL	• Temperature resistance min.	10 °C
• Oil and grease resistance	no	• UV resistant	yes
• Ozone resistance	yes	• Waterproof	no

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>