



CLOTH TAPE FOR MULTIPURPOSE OUTDOOR USE

The Outdoor Tape tesa® 4621 Offers a Range of Benefits

- **Increased safety** as this tape can be effortlessly torn by hand in both vertical and horizontal directions, so no cutting device is needed
- **Time saved on cleaning up** due to the tape being weather resistant for up to 8 weeks, meaning no residues are left behind
- Cloth reinforcement withstands wear and tear from tools, ensuring the tape remains unbroken, which offers a hassle-free removal, **improving the final result**




EASY HANDLING FOR ALL YOUR OUTDOOR APPLICATIONS


While cloth tapes are very useful for many applications, a large portion of the tapes available on the market are not suitable for outdoor use. We have now launched a new product that combines the advantages of a cloth backing with excellent weather resistance.




Masking for the coating of floor markings



Taping lightweight signs onto walls



Bundling of building materials



Fastening of loose objects

Application areas

- Masking for the painting of facades, coating of floor markings, plastering
- Holding protective layers such as plastic films and paper sheets in place
- Fastening and bundling of wires, cables and loose objects
- Plus a variety of further uses like taping lightweight signs onto walls and others

Product features

- Higher efficiency for manual work due to the gentle unwinding of the tape without curling when torn
- The green color is easy to identify so no tape is left behind after use, meaning the work space remains tidy
- High initial adhesion on various surfaces, yet easily repositioned to reduce the overall costs
- Low thickness for maximum conformability

Technical data

Product	Backing	Type of adhesive	Color	Total thickness [µm]	Adhesion to steel [N/cm]	Tensile strength [N/cm]	UV resistance	Dimensions [m:mm]
tesa® 4621	PE extruded cloth	Acrylic	Translucent green	130	3.4	54	8 weeks	50: 19/25/30/38/50/75 50: 1350

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.