



tesa[®] 50560 PVO Bumperfilm DISCONTINUED

Product Information

Midlertidig beskyttelsesfilm for nylig lakkerte overflater

Produktbeskrivelse

tesa[®] 50560 Bumperfilm er en selvklebende kvalitetstape som er utviklet for beskyttelse av sårbare overflater, f.eks. malte støtfangere.

Brukerfordeler:

- Kostnadsbesparelser pga. reduksjon i rektifikasjon og endelig reparasjon
- Beskytter den malte overflater i opptil 6 måneders lagring ute
- Ikke nødvendig med spesialutstyr, sikrer en enkel og rimelig påførings- og fjerningsprosess
- Godt klebestoff til en lang rekke malearbeid, selv under transport (testet ved hastigheter over 160 km/t)
- Enkel å deponere Både materialet og klebestoffet er miljøvennlig

Funksjoner

- Preserves the surface finish, up to 6 months' storage outdoors
- Thick material quality for high protection
- Suitable for die cutting and printing
- Cost saving due to reduction in rectification and final repair
- No special equipment needed, ensuring simple, low-cost application and removal processes
- Good adhesion to the range of paint finishes, even during transportation (tested at speeds higher than 160 km/h / 100 mph)
- Easy disposal - the product is harmless to health and environment and can be disposed to the household or recycling waste

Applikasjon

- Beskytter mot smuss og skraper under montering, transport og lagring av malte plastdeler eller/og malte metalloverflater

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|-----------------------|------------------|-------|
| • Bæremateriale | Polyolefinfilm | • Total tykkelse | 75 µm |
| • Klebetype | PIB (polyisobutylene) | | |

Egenskaper / ytelsesverdier

- | | | | |
|------------------------|---------|-----------------------|-----------|
| • Bruddforlengelse | 450 % | • Kjemikaliebestandig | very good |
| • Bruddstyrke | 16 N/cm | • Lett å fjerne | Ja |
| • Egnet til utstansing | Ja | | |

For latest information on this product please visit <http://l.tesa.com/?ip=50560>



tesa[®] 50560

PV0 Bumperfilm DISCONTINUED

Product Information

Klebekraft

- Klebeevne på Stål 1.7 N/cm

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=50560>