



# tesa® 64606

## Product Information

Montering av klisjéer i forbindelse med flexografisk trykking, særlig postprint av bølgepapp

### Produktbeskrivelse

tesa® 64606 PV3 er en grønn transparent, dobbeltsidig, selvklebende tape på 300 µm / 12 mil tykkelse, med PVC-materiale og gummiklebestoff.

tesa® 64606 PV3 er spesialdesignet for feste av fotopolymerplater i fleksografisk trykkeindustri. tesa® 64606 PV3 er spesielt egnet til bruk på platen før montering av hele sylindere eller mylarfilm-arket, som er vanlig ved bølgepapp postprint.

Klebeevne

- Høy klebeevne og skjæremotstand for pålitelige bruk, selv når sammensetningen lagres over lenger tid
- Høy klebeevne og skjæremotstand sikrer at det ikke er noen kantløft, selv på lengre opplag og ved høyere hastigheter
- På grunn av de optimerte klebeegenskapene kan tapen og platen lett repositioneres under montering

Materialet

- Transparent materiale gjør registreringsmerknader synlige

Innlegg

- Det kreppe innlegget forhindrer luftbobler og at tapen krøller seg
- Innlegget er av silikon, noe som gjør det lett å bruke og fjerne

### Funksjoner

- High adhesion values and shear resistance for reliable application, even when the composite is stored for longer periods
- High adhesion and shear also ensure that there is no edge lifting, even on longer print runs and at higher speeds
- Due to the specially optimised adhesive properties, the tape and plate can be easily repositioned during mounting
- Transparent backing makes register marks clearly visible
- The creped liner prevents air trapping and tape curling
- The liner is siliconized, which means easy application and removal

### Applikasjon

tesa® 64606 PV3 er spesialdesignet for feste av fotopolymerplater i fleksografisk trykkeindustri, spesielt på bølgepapp postprint.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Produktinnhold

- |                 |            |              |                       |
|-----------------|------------|--------------|-----------------------|
| • Bæremateriale | PVC-film   | • Type liner | Kreppet, silikonisert |
| • Klebetype     | Naturgummi |              | PP                    |

For latest information on this product please visit <http://l.tesa.com/?ip=64606>



# tesa<sup>®</sup> 64606

## Product Information

### Egenskaper / ytelsesverdier

- Kategori for tykkelse 300

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=64606>