



tesa® 4331

Product Information



Maskeringstape til bruk ved høye temperaturer

Produktbeskrivelse

tesa® 4331 er en ekstremt temperaturbestandig, flatrygget maskeringstape med følgende kvaliteter:

- sterk vedhefting og høy termisk mostand
- gir knivskarpe maskeringsresultater
- fjernes uten å etterlate kleberester

Funksjoner

- The tape enables sharp color edges and offers excellent paint anchorage.
- The masking tape's silicone adhesive system makes the tape extremely heat-resistant, withstanding extreme temperatures of up to 200°C for as long as 30 minutes at a time.
- Residue-free removability for masking applications
- High adhesion for secure bonding, even adheres to surfaces containing silicone

Applikasjon

- Maskering under høyspent elektrostatisk pulverbelegg
- Stålmøbler og sykehusutstyr
- tesa® 4331 fester seg også til overflater av silikon

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|----------|------------------|--------|
| • Bæremateriale | PET-flis | • Total tykkelse | 110 µm |
| • Klebetype | Silikon | | |

Egenskaper / ytelsesverdier

- | | | | |
|--------------------|---------|--------------------|-----|
| • Bruddforlengelse | 100 % | • Hand tearability | low |
| • Bruddstyrke | 53 N/cm | • Lett å fjerne | Ja |

Klebekraft

- | | |
|---------------------|--------|
| • Klebeevne på Stål | 4 N/cm |
|---------------------|--------|



tesa[®] 4331

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04331>