

tesa® Professional 67001 sPVC Plastering Tape Embossed

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

BærematerialeKlebetype	PVC-film Gummi basert	Total tykkelseFarge	130 μm Gul
Egenskaper / ytelsesverdier			
 Bruddforlengelse Bruddstyrke Aldringsbestandighet (UV) Dugg Egnet til ru overflater Fuktbestandighet 	130 % 22 N/cm good good very good good	 Hand tearability Rette avrivningskanter Slitstyrkebestandighet Temperaturbestandighet, kort varighet Water resistance 	very good good good 60 °C good
Klebekraft			
Klebeevne på Stål	1.6 N/cm		

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



²age 1 of 1 – as of 22/02/24 – nb-NO