



tesa® Dobbelsidig monteringsstape for tapet og gips 10kg / m



Product Information

BNR 77743, 77742

Produktbeskrivelse

Monteringsstape for tapet og gips som holder opptil 10kg / m En permanent måte å montere på strukturerte og ømfintlige overflater.

Funksjoner

- For teksturerte og sensitive innendørs overflater som tapet eller gips
- Holder opptil 10 kg / m*
- For permanente bruksområder
- For optimale resultater må du lese instruksjonsheftet. Maks. 6 kg per bruksområde/gjenstand er anbefalt

Applikasjon

- How to apply – Step by step
1. To ensure the best possible bond, clean the surface of dirt and dust with a dust-free cloth.
 2. Make sure you attach the mounting tape to the rougher surface first. In the case of wallpaper or plaster, this will be the wall. Affix vertical strips that correspond to the entire length of the object. Reinforce the upper portion with shorter strips, since that's where the majority of the weight will be born. Press down firmly across on the entire Mounting Tape surface for at least five seconds.
 3. Remove the protective foil from the tape and position the item on the surface. Take care not to touch the exposed adhesive surface as this could affect the adhesion.
 4. Press firmly on the item for another 5 seconds to ensure an optimal bond with the surface.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|-----------------|-----------------------------|---------|
| • Bæremateriale | PE-skum | • Total tykkelse | 1350 µm |
| • Klebetype | Syntetisk gummi | • Tapens klebekraft opp til | 10 KG/M |



tesa® Dobbelsidig monteringsstape for tapet og gips 10kg / m

Product Information

Egenskaper / ytelsesverdier

• Application temperature from	-10 °C	• Krever batterier	Nei
• Batterier inkl.	Nei	• Løsemiddelfri	Ja
• Bruksområdet	Innendørs	• Motstandsdyktig overfor olje og fett	Nei
• Farlig materiale	Nei	• Ozone resistance	Nei
• Fjernes uten kleberester	Nei	• Temperature resistance max.	40 °C
• Fuktbestandighet	Nei	• Temperature resistance min.	10 °C
• Kan brukes om igjen	Nei	• UV-bestandig	Nei
• Kan brukes om igjen med	_NULL	• Vanntett	Nei
• Kjemikaliebestandig	Nei	• Velegnede overflater	Gips, Tapet

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>