



tesa[®] 4244 PV0



Product Information

Finelinetape til designlakkering

Produktbeskrivelse

tesa[®] 4244 er en fleksibel tape av bløt PVC med naturgummikleber, som kan anvendes til maskering av fine linjer, ved behov for meget skarpe lakkanter, særlig på lakkerte eller ikke lakkerte plastdeler og til lakkopgaver, hvor der anvendes flere farger.

- krymper ikke ved høye temperaturer
- tilpasser sig dimensjonale forandringer under ovntørking
- ingen kantløft og etterlate kleberester etter demaskering
- god tilpasning på multidimensjonale overflater

Funksjoner

- Temperature resistance of up to 140°C/1h
- Conformability with the dimensional change during oven drying
- Good conformability with multidimensional surfaces
- Edge does not lift off and residue-free removal

Applikasjon

Maskering og design, for en lang rekke bruksområder for innlegg

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|------------|------------------|--------|
| • Bæremateriale | PVC-film | • Total tykkelse | 110 µm |
| • Klebetype | Naturgummi | | |

Egenskaper / ytelsesverdier

- | | | | |
|--------------------|-----------|------------------------|-----------|
| • Bruddforlengelse | 237 % | • Egnet til utstansing | Ja |
| • Bruddstyrke | 27 N/cm | • Hand tearability | very good |
| • Brannhemmende | very good | • Lett å fjerne | Ja |

Klebekraft

- | | |
|---------------------|----------|
| • Klebeevne på Stål | 3.7 N/cm |
|---------------------|----------|

Additional Information

tesa[®] 4244 er også tilgjengelig for omforming og formtilskjæring med papirinnlegg 4244 PV4:
Klebeevne på stål = 4.7 N/cm,

For latest information on this product please visit <http://l.tesa.com/?ip=04244>



tesa[®] 4244 PV0

Product Information

Additional Information

avrullingskraft fra innlegg = 14 cN/cm

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04244>