



# tesa<sup>®</sup> 58375

## Product Information



130 µm dobbeltsidig non-woven og flammehemmende tape

### Produktbeskrivelse

tesa<sup>®</sup> 58375 er en gjennomskinnelig, dobbeltsidig non-woven tape utstyrt med flammehemmende klebrig akrylkleber.

Denne tapen er spesialutviklet for batterier med krevende monterings-, laminerings- og konverteringsapplikasjoner og hvor flammehemmende egenskap er en merverdi. Tapen er ikke-brennbar og er dermed spesialdesignet for å innfri kravene til bilbatterier.

### Funksjoner

- Flammehemmende i henhold til UL 94 VTM-0 nivå
- God sammenføringsevne
- Høy langvarig pålitelighet og aldringsmotstand
- I samsvar med RoHS og REACH
- Halogenfri

### Applikasjon

- Montering i batteri- eller lamineringsapplikasjoner krever ytterligere flammehemmende egenskaper.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Klebekraft

- |                                  |          |                                 |          |
|----------------------------------|----------|---------------------------------|----------|
| • ASTM (initial)                 | 8.9 N/cm | • Klebeevne på PI (umiddelbart) | 7.1 N/cm |
| • Klebeevne på PET (umiddelbart) | 7.8 N/cm |                                 |          |



# tesa<sup>®</sup> 58375

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=58375>