

tesa®, tesa® Professional 65538PRO Anti-slip Black/Yellow

Product Information



Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

•	Bæremateriale	PVC film coated with	•	Linerfarge	Gul
		mineral particles	•	Linertykkelse	180 μm
•	Klebetype	Akryl	•	Tapetykkelse	720 μm
•	Total tykkelse	900 μm			

Egenskaper / ytelsesverdier

	Bruddforlengelse	25 %		Hand tearability	good
•	bruddionengeise	25 /0	•	папи цеагаршку	good
•	Bruddstyrke	30 N/cm	•	Kan skrives på	Nei
•	Aldringsbestandighet (UV)	good	•	Kjemikaliebestandig	good
•	Batterier inkl.	Nei	•	Krever batterier	Nei
•	Bestandig over for bløtgjørere	good	•	Lett å fjerne	Nei
•	Egnet til utstansing	Ja	•	Slitstyrkebestandighet	very good
•	Fluoriserende	Nei	•	Temperaturbestandighet, lang	50 °C
•	Fuktbestandighet	very good		varighet	
			•	Water resistance	good

Klebekraft

Klebeevne på Stål
5.8 N/cm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

