



tesa[®] Teppe tape

Product Information



BNR 55735, 55731, 55729

Produktbeskrivelse

tesa[®] Flooring Tape Residue-free Removal er en dobbeltsidig, selvklebende teppe- og PVC-gulvtape som er tekstilforsterket og som fjernes uten at det ligger igjen rester

Funksjoner

- For festing av alle slags tepper og PVC-gulvbelegg
- Fester til mange typer gulv, og kan flyttes uten å etterlate seg rester*
- Dobbeltsidig lim
- Tekstilforsterket
- Lett å rive av for hånd

*Merknad om påsetting: Ikke egnet for gulv i naturstein

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- Klebetype Modifisert akryl
- Total tykkelse 248 µm

Egenskaper / ytelsesverdier

- | | | | |
|----------------------------|-------------------|---------------------------|---------------------------------------------------------------------------------------------------------------|
| • Bruddstyrke | 30 N/cm | • Løsemiddelfri | Ja |
| • Batterier inkl. | Nei | • Materiale | PP (polypropylen) |
| • Bruksområde | Hjemme | • Miljøvennlig emballasje | Nei |
| • Farlig materiale | Nei | • Rivebestandig | Ja |
| • Fjernes uten kleberester | Ja | • Spennbarhet | 80 % |
| • Kjemikaliebestandig | Ja | • Temperaturbestandighet | Ja |
| • Klebekraft | Svært høy vedheft | • UV-bestandig | Ja |
| • Krever batterier | Nei | • Velegnede overflater | Fliser, Tregulv, Murstein, De fleste plasttyper, Glass, Akrylglass, Kartong, Gips, Papir, Metall, Stål, Stein |



tesa[®] Teppe tape

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>