



tesafilm® Invisible

Product Information

BNR 57477, 57333, 57312, 57095, 57649, 57335, 05540, 04148, 57484, 57485, 57660, 57414

Produktbeskrivelse

tesafilm® invisible er en selvklebende tape for høykvalitets hobbyarbeid og papirreparasjoner. Den er nesten usynlig, er kopieringsnøytral og kan skrives på.

Funksjoner

- Nesten usynlig på lyst farget papir
- Kan skrives på med nesten alle slags penner
- Enkel håndtering
- Fotokopinøytral
- Høy aldringsmotstand
- Stille uttrekking
- Enkel og rask å fjerne fra harde overflater
- PP-folie og løsemiddelfritt lim
- Egnert for bruk i alle tilgjengelige tesafilm® dispensere

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|------------------|------------------|-------|
| • Bæremateriale | BOPP | • Total tykkelse | 52 µm |
| • Klebetype | Vannbasert akryl | | |

Egenskaper / ytelsesverdier

- | | | | |
|-----------------------------|---------|------------------------|----------------|
| • Bruddstyrke | 20 N/cm | • Løsemiddelfri | Ja |
| • Aldringsbestandighet (UV) | Ja | • Rivebestandig | Nei |
| • Avrulningskraft n/cm | 1 N/cm | • Skrivbar | Ja |
| • Fotokopinøytral | Ja | • Støysvak avrulning | Ja |
| • Gjennomsiktighet | medium | • Velegnede overflater | Kartong, Papir |
| • Hand tearability | Ja | | |



tesafilm[®] Invisible

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>