



# tesa<sup>®</sup> 4172 Professional

## Product Information



Standard gipstape for profesjonelle - enkel i bruk, for utendørs maskering av glatte overflater under gipsarbeid eller maling, tidsbesparende.

## Produktbeskrivelse

tesa<sup>®</sup> 4172 byggtape er en spesialfremstilt, lettavrullig tape av bløtgjort PVC med flat bæremateriale og god klebeevne. Tapen kan motstå fukt, svake alkaliske oppløsninger, syrer og mange andre kjemikalier.

## Applikasjon

- Utendørs maskering (opp til 4 uker)
- For maskering av glatte overflater under gipsarbeid, maling, gipsing, muring og stukkaturarbeid
- Beskyttelse mot skitt og skade gjennom produksjonsverktøy og materiale
- Kan anvendes i kurver

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Produktinnhold

- |                 |            |                  |        |
|-----------------|------------|------------------|--------|
| • Bæremateriale | Bløt PVC   | • Total tykkelse | 120 µm |
| • Klebetype     | Naturgummi |                  |        |

## Egenskaper / ytelsesverdier

- |               |         |
|---------------|---------|
| • Bruddstyrke | 24 N/cm |
|---------------|---------|

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=04172>