



tesa[®] 4128

Product Information



Førsteklasses tape til overflatebeskyttelse

Produktbeskrivelse

tesa[®] 4128 er en PVC-tape, som er motstandsdyktig over for mekanisk og kjemisk belastning, og er belagt med naturgummikleber med lav styrke. tesa[®] 4128 er brudstærk og lett å fjerne.

Oppbevaringstiden etter ibruktagning bør ikke overskride et år. tesa[®] 4128 kan anvendes utendørs i høyst 3 måneder.

Applikasjon

Maskeringstape for en lang rekke maskeringsbehov

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Additional Information

tesa[®] 4128 design gjør den praktisk å bruke for hånd og passer dessuten til omforming og formtilskjæring. Best før-datoen er maks. 12 måneder ved anbefalte lagringsforhold.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04128>