



tesa[®] 51606

Product Information



Tape av tykk PET-fleece til lyddempning og gli beskyttelse av ledningsnett

Produktbeskrivelse

tesa[®] 51606 er en tape som dokumentert gir god lyddempning og høy slitestand. Den er optimert til bruk på kabelfester.

Egenskaper:

- Gode støydempende egenskaper
- Meget sliperesistent
- Revnebestandig
- Alders- og værbestandig
- Kraftig klebeevne

Applikasjon

Kabelfesting

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Egenskaper / ytelsesverdier

• Bruddforlengelse	85 %	• Avrullingskraft (Rull bredde ≤ 9mm)	7.5 N/roll (30 m/min)
• Bruddstyrke	55 N/cm	• Lyddempning (LV312)	D
• Abrasion resistance (10mm mandrel)	Class D (acc. to LV312)	• Temperaturbestandighet (3000h)	105 °C
• Abrasion resistance (5mm mandrel)	Class C (acc. to LV312)	• Temperature resistance min.	-40 °C
• Avrullingskraft (Rull bredde > 9mm)	7.5 N/roll (30 m/min)	• Thermal conductivity x-y-direction	0.066 W/mK

Klebekraft

- Klebeevne på Stål 5.5 N/cm



tesa[®] 51606

Product Information

Additional Information

Temperaturmotstand målt ved 30000 t ifølge LV312

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51606>