

tesa® 51408

Product Information



Flammehemmende, Kapton-maskerinstape med høy kvalitet

Produktbeskrivelse

tesa® 51408 (Kaptone®-materiale med silikon klebestoff) motstår høye temperaturer og har en kraftig klebeevne

Applikasjon

51408 motstår høye temperaturer i en begrenset periode (250 °C = 1000 timer, 350 °C = 10 timer).

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

•	Bæremateriale	Polyimide	•	Total tykkelse	65 μm
•	Klebetype	Silikon			

Egenskaper / ytelsesverdier

•	Temperaturbestandighet	260 °C	•	Gjennomslagspenning	6000 V
•	Bruddforlengelse	70 %	•	Isolasjonsklasse	Н
•	Bruddstyrke	46 N/cm			

Klebekraft

Klebeevne på Stål
2.8 N/cm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.