



tesa® 60951

Product Information



Antisklitape - svart/gul

Produktbeskrivelse

tesa® 60951 er en antisklitape med et PVC-lag, belagt med aluminiumoksid for å sikre trygt fotfeste. Den svart og gule antisklitapen er spesielt slitesterk og elastisk. Den er ideell for å sikre arbeidsområder som utgjør en økt ulykkesrisiko. Denne tapen beholder antisklieffekten i opp til to år med ordinær bruk. Den kan lett rives for hånd og etter bruk fjernes den enkelt uten å etterlate rester.

Funksjoner

- Innen- og utendørs bruk * Bruksområder hvor det er nødvendig med et sikkert grep under føttene * Svart-gul (tesa® 60951): markering av veldig glatte overflater

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|--|------------------|--------|
| • Bæremateriale | PVC film coated with mineral particles | • Total tykkelse | 900 µm |
| • Klebetype | Akryl | | |

Egenskaper / ytelsesverdier

- | | | | |
|--------------------------|-----------|-----------------------|-----------|
| • Temperaturbestandighet | -5 to +50 | • Fuktbestandighet | very good |
| • Bruddforlengelse | 25 % | • Hand tearability | good |
| • Bruddstyrke | 30 N/cm | • Kjemikaliebestandig | good |

Klebekraft

- | | |
|---------------------|----------|
| • Klebeevne på Stål | 5.8 N/cm |
|---------------------|----------|

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.