

tesamoll® STANDARD I-profil

BNR 5559

tesamoll® Standard I-profile er en universell tetningslist som er ideell for isolering av dører og vinduer ved å tette åpninger på mellom 1 og 3,5 mm.

Funksjoner

- Selvklebende, langtidsholdbar tetningslist
- Forsegler alle åpninger fra 1 til 3,5 mm
- Holdbarhet: 4 år
- Myk og fleksibel
- Tørk ren

Produktegenskaper

- | | | | |
|---------------------------|--------|-----------------------|------------|
| • Applicationfield | Hjemme | • Solvent free | Ja |
| • Holdbarhet | 4 Year | • Batteries required | Nei |
| • Humidity resistant | Nei | • Tetter sprekker fra | 1 - 3.5 mm |
| • Resistance to chemicals | No | • Batteries included | Nei |

Tekniske data

- | | | | |
|--------------------------|-----------------|----------------------------------|--------|
| • Residue-free removable | Nei | • Temperature resistant | Ja |
| • Klebetype | Syntetisk gummi | • Temperaturbestandighet fra | -50 °C |
| • Bæremateriale | PE | • Temperaturbestandighet opp til | 50 °C |

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=NaN>