



tesa[®] extra Power Eco Repair

Product Information

BNR 56430, 56431, 56432

Produktbeskrivelse

Hvis du vil ha en høytytende sølvtape som gir ekstra slitestyrke og lang holdbarhet, er tesa[®] extra Power Eco det miljøvennlige alternativet.

Funksjoner

- For håndverk, reparasjon, festing, bunting, forsterking, merking og mye mer
- Rivebestandig, men enkel å rive av for hånd
- Kan skrives på
- Finnes i sort, grått og hvitt

Miljøhensyn:

- Naturlige, bærekraftige fibre
- 64 % biobasert materiale
- Løsemiddelfritt naturgummilim

Emballering:

- 80 % resirkulert papp

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|---------------------|------------------|--------|
| • Bæremateriale | Akrylbelagt tekstil | • Total tykkelse | 280 µm |
| • Klebetype | Naturgummi | | |

Egenskaper / ytelsesverdier

- | | | | |
|--|-------------|------------------------|---|
| • Temperaturbestandighet | Ja | • Ozone resistance | Ja |
| • Bruddstyrke | 70 N/cm | • Rivebestandig | Ja |
| • Aldringsbestandighet (UV) | Ja | • Skrivbar | Ja |
| • Fjernes uten kleberester | Ja | • Spennbarhet | 9 % |
| • Fuktbestandighet | Ja | • UV-bestandig | Ja |
| • Hand tearability | Ja | • Vanntett | Nei |
| • Klebekraft | Høy vedheft | • Velegnede overflater | Jevnt tre, Fliser, Murstein, Glass, Akrylglass, Kartong, Gips, Papir, Metall, Stål, Stein |
| • Løsemiddelfri | Ja | | |
| • Motstandsdyktig overfor olje og fett | Nei | • Water resistance | Ja |

For latest information on this product please visit <http://l.tesa.com/?cp=56430>



tesa[®] extra Power Eco Repair

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=56430>