

tesa[®] Justerbar limskruer for tapet og gips 1 kg

BNR 77775

Høydejusterbar limskruer for opptil 1 kg. Perfekt for montering av pyntegjenstander på strukturerte og ømfintlige overflater som tapet eller gips.

Funksjoner

- For teksturerte og sensitive overflater som tapet eller gips
- Holder opptil 1kg* per skruer eller 2 kg med 2 skruer
- Kan justeres i høyden for oppretting* Kan fjernes uten å etterlate merker
- Gjenbrukbar med en ny strimmel
- For optimale resultater kan du lese instruksjonsheftet

Produktegenskaper

- | | | | |
|-----------------------------|--------------|----------------------|--------------------------------|
| • Type of tape | Dobbeltsidig | • Solvent free | Ja |
| • Transparent | Nei | • Suitable surfaces | Gips, Tapet |
| • UV-resistant | Nei | • Reusable | Ja |
| • Bestandighet mot vann | Nei | • Waterproof | Nei |
| • Humidity resistant | Nei | • Reusable with | sms-refill-strip-wallpaper-1kg |
| • Oil- and grease-resistant | Nei | • Batteries required | Nei |
| • Ozone resistant | Nei | • Batteries included | Nei |
| • Resistance to chemicals | No | | |

Tekniske data

- | | | | |
|---------------------------|-----------------|----------------------------------|-------|
| • Application temperature | min. 15° C | • Temperaturbestandighet fra | 5 °C |
| • Area of use | Innendørs | • Temperaturbestandighet opp til | 35 °C |
| • Materiale | PS (polystyrol) | • Silicone free | Ja |
| • Residue-free removable | Ja | • Hazard material | Nei |
| • Klebetype | Syntetisk gummi | | |

tesa[®] Justerbar limskrue for tapet og gips 1 kg

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=NaN>