



# tesa<sup>®</sup> 4247 PV2



## Product Information

Emballasjetape lett avrullbar PVC

### Produktbeskrivelse

tesa<sup>®</sup> 4247 er en emballasjetape, som består av en PVC-folie med en naturgummikleber. Takket være releas coating er tesa<sup>®</sup> 4247 lett avrullbar og velegnet til maskinbearbeiding.

Ledende resirkulerings-virksomheter og papirfabrikker har bekreftet, at resirkuleringsprosessen for pappavfall ikke forstyrres.

### Applikasjon

tesa<sup>®</sup> 4247 benyttes til manuell og automatisk forsegling av mellomtunge kartonger.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Produktinnhold

- |                 |            |                  |       |
|-----------------|------------|------------------|-------|
| • Bæremateriale | PVC-film   | • Total tykkelse | 54 µm |
| • Klebetype     | Naturgummi |                  |       |

### Egenskaper / ytelsesverdier

- |                    |         |                        |    |
|--------------------|---------|------------------------|----|
| • Bruddforlengelse | 75 %    | • Automatisk påsetting | Ja |
| • Bruddstyrke      | 47 N/cm |                        |    |

### Klebekraft

- |                     |          |
|---------------------|----------|
| • Klebeevne på Stål | 2.4 N/cm |
|---------------------|----------|

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=04247>