



# tesa<sup>®</sup> 53166

## Product Information



Belagt tekstiltape for bunting av kabler og skjøting

### Produktbeskrivelse

tesa<sup>®</sup> 53166 er en ekstrudert polyetylen-tape Den består av en 55 maskers vevd PET/rayon med trykkfølsomt gummiklebestoff.

Egenskaper:

- Kraftig klebeevne
- Meget lett å skille ad for hånd
- Vann-resistent
- Alders-resistent
- Fleksibel
- Lav avrullingskraft
- 105°/3000t

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Produktinnhold

- |                 |             |                  |        |
|-----------------|-------------|------------------|--------|
| • Bæremateriale | Vev (Rayon) | • Total tykkelse | 260 µm |
| • Klebetype     | Naturgummi  |                  |        |

### Egenskaper / ytelsesverdier

- |                    |         |                                       |                       |
|--------------------|---------|---------------------------------------|-----------------------|
| • Bruddforlengelse | 9 %     | • Avrullingskraft (Rull bredde > 9mm) | 3.5 N/roll (30 m/min) |
| • Bruddstyrke      | 52 N/cm | • Avrullingskraft (Rull bredde ≤ 9mm) | 3.5 N/roll (30 m/min) |

### Klebekraft

- |                     |          |
|---------------------|----------|
| • Klebeevne på Stål | 3.4 N/cm |
|---------------------|----------|



# tesa<sup>®</sup> 53166

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=53166>