

tesa® SPAA Shower Rail, Self-Adhesive, Chromed Metal & Plastic

Product Information

BNR 40341

Product Description

No drilling is needed to securely mount the self-adhesive tesa® Spaa shower rail. Surfaces stay undamaged. The chrome plating gives the bar a beautiful shine. It can be taken down quickly and without a trace at your convenience. Reuse in another location is simple, requiring only a new adapter BK30-2.

Product Features

- Shower rail, with tesa® Power.Kit technology (all-in-one adhesive mounting solution)
- · Chrome-plated, plastic & chrome-plated metal elements
- · Reliable hold, waterproof, guaranteed stainless
- · Suitable for tiles, metal, natural stone, marble, concrete, wood, glass and many types of plastic
- · Does not work on wallpaper, stucco and other surfaces with non-stick coating
- Effortless to take down without a trace, can be attached elsewhere with adapter BK30-2
- · Mounting without drilling
- · Includes conical slider, tiltable
- · Bar length: 705mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Type of adhesive	Silane modified	•	Hook shape	Round
		polymer			
•	Holding power up to	12 Kg			

Properties/Performance Values

•	Applicationfield	Bathroom	•	Residue-free removability	yes
•	Area of use	Indoor	•	Reusable	yes
•	Batteries included	no	•	Reusable with	Adapter BK30-2
•	Batteries required	no	•	Shape of wall piece	Round
•	Chemical Resistance	no	•	Solvent free	yes
•	Curing time	12 hour(s)	•	Suitable surfaces	Glazed Tiles, Marble,
•	Design series	tesa® SPAA			Glass, Metal, Stone,
•	Humidity resistance	yes			Concrete, Even wood,
•	Material	Chromed metal,			Most plastics
		Chromed plastic	•	UV resistant	yes

UV resistant yesWaterproof yes



tesa® SPAA Shower Rail, Self-Adhesive, Chromed Metal & Plastic

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

