

## tesa® Powerstrips Waterproof Duo Hook, Metal-Plastic



## **Product Information**

BNR 59785

#### **Product Features**

- · Easy to mount without drilling, screws or nails
- · Strong hold up to 3kg
- Removable without a trace due to the Powerstrips Waterproof technology
- Material combination stainless steel & plastic
- Usable on tiles, glass, etc. in humid rooms or directly in the shower\*
- Especially developed for wet areas (e.g. shower, bath tub etc.)
- · Ideal to hold e.g. a sponge, washrag, etc. if needed in the shower
- · Reusable with tesa Powerstrips Waterproof Large

## **Application Fields**

How to apply:

- 1. Clean the surface with alcohol or silicone-free glass cleaner
- 2. Take the included waterproof primer tissue and wipe over the surface for bonding preparation wait for 10 seconds minimum
- 3. Apply the Powerstrip Waterproof Large strips on the surface press for 5 seconds minimum
- 4. Disengage the base plate of the hook and stick it onto the strips press for 5 seconds minimum
- 5. Let the hook slide down on the base plate until it is locked

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

Type of adhesive synthetic rubber
Hook shape Rectangular
Holding power up to 3 Kg
Silicone free yes

<sup>\*</sup>Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous material



# tesa® Powerstrips Waterproof Duo Hook, Metal-Plastic

## **Product Information**

## **Properties/Performance Values**

•	Application temperature from	+15 °C	•	Residue-free removability	yes
•	Application temperature to	+35 °C	•	Reusable	yes
•	Applicationfield	Bathroom, Kitchen	•	Reusable with	Powerstrips
•	Area of use	Indoor			Waterproof Large
•	Batteries included	no	•	Solvent free	yes
•	Batteries required	no	•	Suitable surfaces	Even wood, Tiles,
•	Chemical Resistance	no			Most plastics, Glass,
•	Hazard material	yes			Acrylic glass, Steel,
•	Material	Stainless steel, Plastic			Metal
•	Oil and grease resistance	no	•	Temperature resistance	yes
•	Ozone resistance	no	•	Temperature resistance max.	35 °C
			•	Temperature resistance min.	15 °C
			•	UV resistant	no
			•	Waterproof	yes

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

