



# tesa<sup>®</sup> 53398

## Product Information



Clean removal high strength mono filament tape

### Product Description

tesa<sup>®</sup> 53398 is a high-strength, polyester backed, fiberglass reinforced mono filament tape.

### Product Features

- tesa<sup>®</sup> 53398 has a high tack and high shear resistant adhesive system
- tesa<sup>®</sup> 53398 has excellent aging properties and assures clean removal from many substrates

### Application Fields

- Securing of metal coils for end-tabling
- Splicing of metal coils for processing
- Bundling and reinforcement of heavy goods, e.g. metal pipes

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                       |                   |        |
|--------------------|-----------------------|-------------------|--------|
| • Backing          | glassfibre / PET film | • Total thickness | 195 µm |
| • Type of adhesive | synthetic rubber      |                   |        |

### Properties/Performance Values

- |                    |          |
|--------------------|----------|
| • Tensile strength | 800 N/cm |
|--------------------|----------|

### Adhesion to Values

- |         |        |
|---------|--------|
| • Steel | 6 N/cm |
|---------|--------|



# tesa<sup>®</sup> 53398

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=53398>