



**Product Information** 



Basic tear tape

### **Product Description**

tesa® 51210 is a self-adhesive tensilised polypropylene tear tape with a synthetic rubber adhesive system.

tesa® 51210 exhibits excellent tack, adhesion and shear resistance on a variety of corrugated and solid cardboard surfaces.

The product is recommended for high unwinding speeds in automatic production.

## **Application Fields**

- Tear strip for medium grades of solid board and double-wall corrugated cardboard
- Tear strip for use on detergent and consumer cartons, padded shipping envelopes, express delivery and courier
  envelopes

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

<ul><li>Backing</li><li>Type of adhesive</li></ul>	MOPP synthetic rubber	Total thickness	89 µm
Properties/Performance Values			
Elongation at break	25 %	Tensile strength	130 N/cm
Adhesian to Values			

#### Adhesion to Values

Steel 5.5 N/cm





**Product Information** 

**Additional Information** 

Available in red.

# Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 - as of 17/02/24 - en-US