



tesa® 62009

Product Information



Card Labels

Product Description

tesa® 62009 is a double-sided adhesive label for the automatic or manual fixing of cards to paper.

After the mailing process the card can be removed easily without leaving any residues or stains. Therefore tesa® 62009 is an optimised solution for the mailing of all card types.

Product Features

- Easily removable without leaving residues or damaging the card
- High adhesive reliability to all card surfaces and materials
- High processing reliability
- Up to 2,500 labels/hr can be applied automatically
- The open side of the label is made of a reversible adhesive which is optimised for the temporary attachment to all card materials.
- The reverse side of the label, which lies on the release liner, consists of a permanent adhesive that enables a secure and reliable fixing to paper.

Application Fields

Mailing of cards

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|--------|
| • Backing | PVC with PP | • Total thickness | 140 µm |
| • Type of adhesive | modified acrylic | • Color | white |
| • Type of liner | glassine | | |

Properties/Performance Values

- | | |
|-----------------------------|-----|
| • Residue-free removability | yes |
|-----------------------------|-----|

Adhesion to Values

- | | | | |
|--------------------------|--------|--------------------------|----------|
| • Steel (permanent side) | 3 N/cm | • Steel (removable side) | 0.4 N/cm |
|--------------------------|--------|--------------------------|----------|

Additional Information

Standard version:

Label format: 38mm x 17mm

For latest information on this product please visit <http://l.tesa.com/?ip=62009>



tesa[®] 62009

Product Information

Additional Information

Labels/roll: 4000 pcs.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=62009>