

Paper-based packaging closing tape

tesa[®] 61346 for secure transport closing and recyclable paper-based packaging solutions



1 m

Packaging made of paper and board material protects valuable goods during transport and storage. Part of a functional and well-perceived packaging is the convenience of quick and easy 'box closing' without requiring additional tools or equipment. At the same time, recyclability is – and should be – becoming more and more important. This can be achieved by 'mono-material packaging', completely avoiding the use of plastic material, which also applies to integrated closing tapes.

Introducing tesa® 61346

Our paper-based closing tape tesa® 61346 enables secure closing of cardboard boxes or mailer bags and upon disposal, the tape can be recycled along with the box material.

At tesa, we want to increasingly use our expertise to develop products with a contribution to sustainability. tesa® 61346 ticks the following boxes when it comes to sustainable aspects:

- Recyclable: disposable with the board material
- Paper backing from sustainably managed sources
- Solvent-free coating process
- 100% recycled paper core







Our new tesa® 61346 paper-based closing tape is designed for recyclable and secure closing of boxes, packages, or mailing bags made of corrugated board, cardboard, or paper. Integrated into box designs, the boxes can easily be closed without requiring any additional tools or equipment. The tape's innovative, strong paper backing is combined with a high-tack adhesive, ensuring a reliable bond also on board with recycled content.

tesa[®] 61346 can be applied in-line during the corrugated board manufacturing process which was succesfully tested on the market-leading applicators. During box processing and finishing, tesa[®] 61346 can also be applied with off-line market standard applicator systems. Contact your tesa sales representative today with your individual requirements to sample tesa[®] 61346.

tesa® 61346 main benefits at a glance



Technical data

	tesa® 61346	
Backing	Paper	White paper liner
Color	White	
Total thickness	185 μm	Synthetic rubber adhesive Paper backing Synthetic rubber adhesive
Type of adhesive	Synthetic rubber solvent-free	
Elongation at break	1.7%	
Tensile strength	40 N/cm	
Adhesion to steel	10 N/cm	

tesa SE Phone: +49 40 88899 0 tesa.com/company/locations tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.