



# tesa<sup>®</sup> PVC Plastering Tape

## Product Information

BNR 55487

### Product Description

The tesa<sup>®</sup> PVC Plastering Tape is a high-quality tape which has been specially developed for outdoor use. It can be used as an excellent masking tape for plastering work, as a convenient solution to bundle items safely together or to fix objects in place. The tape is made of PVC backing material and provides great adhesive strength, even on slightly rough surfaces.

It has excellent UV-resistance for up to 6 weeks. Achieve great looking and high-quality results with tesa<sup>®</sup> PVC Plastering Tape.

### Product Features

- Ideal for high-quality outdoor applications, protects various objects
- Versatile application: Can be used in different ways - from masking and bundling to fixing with a secure grip
- Strong and reliable: Sturdy build guarantees powerful adhesive performance, even on slightly rough surfaces
- Durable: Can be applied in a wide temperature range and is heat- and mild cold-resistant
- UV-sunlight resistant for up to 6 weeks
- Good for plastering as well as keeping items sorted and organised for later use
- Hand-tearable for convenient use

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                |                   |        |
|--------------------|----------------|-------------------|--------|
| • Backing          | soft PVC       | • Total thickness | 120 µm |
| • Type of adhesive | natural rubber |                   |        |

### Properties/Performance Values

- |                      |         |                      |     |
|----------------------|---------|----------------------|-----|
| • Tensile strength   | 22 N/cm | • Batteries required | no  |
| • Batteries included | no      | • UV resistant       | yes |



# tesa<sup>®</sup> PVC Plastering Tape

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>