

# tesa® EKKRO Robe Hook, Self-Adhesive, Chromed Metal



**Product Information** 

### BNR 40236

## **Product Description**

Reliably wall-mounting the tesa<sup>®</sup> Ekkro robe hook is an easy affair, and its glossy clean look makes it a delightful piece of bathroom décor. No drilling is involved, so no surfaces are damaged. Moreover, the hook can be conveniently removed without any residue and reused with a new adapter BK20.

## **Product Features**

- Robe hook, with tesa® Power.Kit technology (all-in-one adhesive mounting solution)
- High gloss chrome-plated metal, angular style, multi-purpose
- Safely wall-mounted, waterproof, guaranteed stainless
- Works on tiles, metal, natural stone, marble, concrete, wood, glass and many types of plastic
- Does not work on wallpaper, stucco and other surfaces with non-stick coating
- Effortless removal without residue, reusable with adapter BK20
- Simple to fasten, no drilling needed
- Product dimensions: 50mm x 50mm x 63mm

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## **Product Construction**

• T	ype of adhesive	Silane modified	•	Hook shape	Square
		polymer			
•  -	lolding power up to	6 Kg			

## **Properties/Performance Values**

<ul> <li>Are</li> <li>Batt</li> <li>Batt</li> <li>Che</li> <li>Cur</li> <li>Des</li> </ul>	olicationfield a of use teries included teries required emical Resistance ing time sign series erial	Bathroom Indoor no no 12 hour(s) tesa® EKKRO Chromed metal	•	Residue-free removability Reusable Reusable with Shape of wall piece Solvent free Suitable surfaces	yes yes Adapter BK20 Rectangular yes Glazed Tiles, Marble, Glass, Metal, Stone, Concrete, Even wood,
	nber of hooks	Single, Double	•	UV resistant Waterproof	Most plastics yes yes



# tesa® EKKRO Robe Hook, Self-Adhesive, Chromed Metal

**Product Information** 

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 29/02/24 – en-US