

52115 TP

Product Information



Product Description

tesa® Softprint 52115 TP is a double-coated foam tape, designed specifically for mounting photopolymer plates with a thickness of 1.14mm (0.045") or 1.70mm (0.067") in flexographic label printing.

The medium hard foam makes this the ideal solution for printing line work and texts.

Product Features

- Foam properties: Highly compressible foam, with superior recovery behavior for excellent print quality. Long Isting recovery characteristic for extended and high speed print runs. Low thickness tolerances for quick print preparation and reduced waste
- Adhesive properties: High bonding on open side to steel cylinder or sleeve to avoid plate movement. Sufficient
 bonding to plate to avoid edge lifting or plate movement. Non increasing, tailored bonding power for easy repositioning
 and especially for easy demounting of thinner plates. Very cohesive adhesive structure for demounting without
 adhesive residues.
- Additional properties: The structured PP-liner prevents the formation of air pockets when plate mounting. Blue color marking indicates the medium hard foam quality.

Application Fields

tesa® Softprint 52115 TP is a $380\mu m$ (15 mil) category double-coated foam tape, designed specifically for mounting photopolymer plates with a thickness of 1.14 mm (0.045") or 1.70 mm (0.067") in flexographic label printing.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing	PE foam with film	•	Total thickness	430 μm
		lamination	•	Color	blue

Type of adhesive tackified acrylicType of liner PP

Properties/Performance Values

•	Color of foam	white	•	Hardness	medium-hard
•	Color of logo	blue	•	Thickness category	380



52115 TP

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

