

# tesa<sup>®</sup> 4104 transparent



## Product Information

Multi-purpose self adhesive packaging adhesive film

## Product Description

tesa<sup>®</sup> 4104 is a transparent premium packaging tape based on a PVC-film backing and a natural rubber adhesive.

## Product Features

- Conformable yet robust filmic backing
- Very good tack and immediate adhesion on numerous substrates
- Suitable for more demanding environmental conditions such as higher temperatures or humidity
- Smooth and silent unwinding

## Application Fields

- Sealing small boxes from card-board or plastic
- Sealing tins and bags

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                |                   |       |
|--------------------|----------------|-------------------|-------|
| • Backing          | PVC film       | • Total thickness | 67 µm |
| • Type of adhesive | natural rubber |                   |       |

## Product Assortment

- |                    |             |
|--------------------|-------------|
| • Available colors | transparent |
|--------------------|-------------|

## Properties/Performance Values

- |                         |         |                       |     |
|-------------------------|---------|-----------------------|-----|
| • Elongation at break   | 60 %    | • Low noise unwinding | yes |
| • Tensile strength      | 60 N/cm | • Printability        | yes |
| • Automatic application | no      |                       |     |

## Adhesion to Values

- |         |          |
|---------|----------|
| • Steel | 2.3 N/cm |
|---------|----------|

# tesa<sup>®</sup> 4104 transparent

Product Information

## Additional Information

tesa<sup>®</sup> 4104 is easily printable and available in many product width variants. For colour variants refer to tesa<sup>®</sup> 60404.

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=4104>