

tesa[®] 4204 PVO



Product Information

Filmic Packaging Tape

Product Description

tesa[®] 4204 is a versatile packaging and bag sealing tape based on a PVC-film backing and a natural rubber adhesive. It shows excellent performance on all kind of cardboards and secures a safe closure. It is also available in smaller widths such as 9, 12, 19 and 25mm. The natural rubber adhesive system is designed to show best results for applications on different kind of surfaces.

Product Features

- Good adhesion even on recycled cartons
- Excellent tack and long-lasting adhesion
- Silent unwinding
- Ideal for storage in extreme temperature conditions and high moisture

Application Fields

- Sealing boxes from card-board or plastic
- Sealing tins and bags
- Suitable for marking applications

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|-------|
| • Backing | PVC film | • Total thickness | 52 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-------------------------|---------|-----------------------|-----|
| • Elongation at break | 75 % | • Humidity resistance | yes |
| • Tensile strength | 40 N/cm | • Low noise unwinding | yes |
| • Automatic application | yes | | |

Adhesion to Values

- | | |
|---------|--------|
| • Steel | 2 N/cm |
|---------|--------|

tesa[®] 4204 PV0

Product Information

Additional Information

tesa 4204 PV0 is available in white, transparent and brown. For colored variants in red, blue, green and yellow refer to tesa 60404.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=4204>