

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 69

Revision: 06.12.2022

*** SECTION 1: Identification of the substance/mixture and of the company/undertaking**

· **1.1 Product identifier**

· **Trade name** tesa Spray Glue extra strong / Spray Glue Mounting

· **Article number:** tesa 60022 (500ml)
60022
57984
58613

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture**

Adhesives

· **1.3 Manufacturer/Supplier:**

tesa SE
Hugo-Kirchberg-Strasse 1
D-22848 Norderstedt
Tel.: +49-40-88899-101
Germany

· **Informing department:**

tesa SE, Corporate Regulatory Affairs
SDS@tesa.com, Tel.: +49-40-88899-6954

· **1.4 Emergency telephone number:**

Poisons Information Centre in Germany:
Poison Information Centre North
Centre of Pharmacology and Toxicology of University Goettingen
Robert-Koch Strasse 40, D-37075 Goettingen
Telephone: +49 551 38 31 80
Emergency telephone: +49 551 19240 (24 hours available)

Poisons Information Centres in Europe:
see WHO website:
<http://www.who.int/ipcs/poisons/centre/directory/euro/en/>

UNITED KINGDOM:
The UK National Poisons Emergency number is 0870 600 6266
London:
Emergency 24 hour telephone: +44 (0)20 7188 0100
Guy's & St Thomas' Poisons Unit
Medical Toxicology Information Services
Mary Sheridan House, Guy's Hospital, Great Maze Pond, London SE1 9RT
Reception Headquarters
tesa SE, Hugo-Kirchberg-Str. 1, 22848 Norderstedt, Germany
Phone: +49 40 88899 2667 (Mon.-Thurs. 07:00-18:00h, Fr. 07:00-15:00h)

*** SECTION 2: Hazards identification**

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



flame

Aerosol 1

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 69

Revision: 06.12.2022

Trade name tesa Spray Glue extra strong / Spray Glue Mounting

(Contd. of page 1)



Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

2.2 Label elements
Labelling according to Regulation (EC) No 1272/2008
Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07

Signal word

Danger

Hazard-determining components of labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics methyl acetate

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P103 Read carefully and follow all instructions.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P271 Use only outdoors or in a well-ventilated area.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P405 Store locked up.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

The product does not contain any elutable organically bound halogen compounds that can lead to an increase in the AOX value in the context of waste water analysis.

Results of PBT and vPvB assessment

· **PBT:** Not classified
 · **vPvB:** Not classified

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 69

Revision: 06.12.2022

Trade name **tesa Spray Glue extra strong / Spray Glue Mounting**















(Contd. of page 2)

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with non-hazardous or non-declarable substances.

Dangerous components:

CAS: 79-20-9 EINECS: 201-185-2 Reg.nr.: 01-2119459211-47-xxxx	methyl acetate  Flam. Liq. 2, H225  Eye Irrit. 2, H319; STOT SE 3, H336	<25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane, pure  Flam. Gas 1A, H220  Acute Tox. 3, H331 Press. Gas (Comp.), H280	<25%
CAS: 64742-49-0 EC number: 921-024-6	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics  Flam. Liq. 2, H225  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; STOT SE 3, H336	<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane liquefied  Flam. Gas 1A, H220 Press. Gas (Comp.), H280	<25%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane  Flam. Gas 1A, H220 Press. Gas (Comp.), H280	<10%
CAS: 110-54-3 EINECS: 203-777-6 Reg.nr.: 01-2119480412-44-xxxx	n-hexane  Flam. Liq. 2, H225  Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; STOT SE 3, H336	<1%

Regulation (EC) No 648/2004 on detergents / Labelling for contents

not applicable

Additional information

Asp. Tox. 1, H304 of contained components is not applicable to the aerosol present in aerosol dispensers according to EC 1272/2008 Annex I, 1.3.3.
The wording of the listed hazard statements can be found in section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Take affected persons into the open air.
Do not leave affected persons unsupervised.
Instantly remove any clothing soiled by the product.

After inhalation

In case of unconsciousness bring patient into stable side position for transport.

After skin contact

Instantly wash with water and soap and rinse thoroughly.

After eye contact

Rinse opened eye for several minutes under running water. Consult a doctor if symptoms persist.

After swallowing

Consult a doctor if symptoms persist

4.2 Most important symptoms and effects, both acute and delayed

Dazedness
May cause drowsiness / dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 69

Revision: 06.12.2022


Trade name **tesa Spray Glue extra strong / Spray Glue Mounting**

(Contd. of page 3)


SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol-resistant foam.
- **5.2 Special hazards arising from the substance or mixture** In the event of a fire, may be released:
Nitrogen oxides (NO_x)
Under certain fire conditions, traces of other toxic substances cannot be excluded.
- **5.3 Advice for firefighters**
- **Protective equipment:** Put on breathing apparatus.
Do not inhale explosion gases or combustion gases.
- **Additional information** Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation
Keep away from ignition sources
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  Do not allow to enter drains or water courses.
Inform responsible authorities in case of spilling into water or sewage system.
- **6.3 Methods and material for containment and cleaning up:** Dispose of contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:** Do not spray on flames or red-hot objects.
 Keep ignition sources away - Do not smoke.
Beware: Container is pressurized. Keep away from direct sun exposure and temperatures over 50°C. Do not open by force or throw into fire even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Store away from flammable substances.

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 69

Revision: 06.12.2022

Trade name tesa Spray Glue extra strong / Spray Glue Mounting

(Contd. of page 4)

- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

* SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical systems:** No further data; see item 7.

· **Components with critical values that require monitoring at the workplace:**

79-20-9 methyl acetate

WEL	Short-term value: 770 mg/m ³ , 250 ppm Long-term value: 616 mg/m ³ , 200 ppm
-----	---

106-97-8 butane, pure

WEL	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
-----	---

110-54-3 n-hexane

WEL	Long-term value: 72 mg/m ³ , 20 ppm
-----	--

- **Additional information:** The lists that were valid during the compilation were used as basis.

- **8.2 Exposure controls**
- **Personal protective equipment**
- **General protective and hygienic measures**

The usual precautionary measures should be adhered to in handling the chemicals. Keep away from foodstuffs, beverages and food. Instantly remove any contaminated garments. Wash hands before breaks and at the end of the work. Avoid contact with the eyes and skin.

- **Breathing equipment:** Not necessary if room is well-ventilated.
Use breathing filter A2



In case of short term exposure use respiratory protection. In case of intensive or longer exposure use respiratory protection equipment independent from ambient air.

- **Protection of hands:** The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**



Nitrile rubber, NBR

use solvent stable gloves.

- **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Not required.
- **Body protection:** Not necessary at proper use

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 69

Revision: 06.12.2022

Trade name tesa Spray Glue extra strong / Spray Glue Mounting

(Contd. of page 5)

* SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Aerosol
Colour:	Light yellow
· Smell:	Solvent-like
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	-44 °C
· Flash point:	-97 °C
· Inflammability (solid, gaseous)	Not applicable.
· Ignition temperature:	470 °C
· Decomposition temperature:	Not determined.
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Not determined.
· Critical values for explosion:	
Lower:	1.5 Vol %
Upper:	16 Vol %
· Steam pressure at 20 °C:	8,300 hPa
· Density at 20 °C	0.72 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
dynamic:	Not determined.
kinematic:	Not determined.
· Solvent content:	
Organic solvents:	43 %
Solids content:	18.5 %
· 9.2 Other information	The specified boiling point of -44 °C is the boiling point of propane and it is nearly equivalent to the initial boiling point of the mixture. For adhesive applications, this temperature range is not relevant.

* SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 69

Revision: 06.12.2022

Trade name tesa Spray Glue extra strong / Spray Glue Mounting

(Contd. of page 6)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

* SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Primary irritant effect:**
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** May be fatal if swallowed and enters airways.

* SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **According to recipe contains the following heavy metals and compounds according to EC guideline NO. 76/464 EC:**
 - Free of heavy metals (Pb, Cd, Hg, Cr6+)
 - Free of polybrominated biphenyls (PBBs) and polybrominated diphenyl ethers (PBDEs) in accordance with the RoHS Directive.
- **General notes:**
 - Harmful to aquatic organisms
 - Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.
 - Water hazard class 2 (Self-assessment): hazardous for water.
 - Prevent product from reaching ground water, water bodies or sewage systems.
 - Danger to drinking water even if small quantities leak into soil.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 69

Revision: 06.12.2022

Trade name **tesa Spray Glue extra strong / Spray Glue Mounting**

(Contd. of page 7)

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**
· **Recommendation**



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Must be specially treated under adherence to official regulations.

· **Additional information about the European waste catalogue:**

Disposal should be carried out in compliance with the legal regulations after consultation with the competent local authority and the disposal company in a suitable facility approved for this purpose. According to EU Directive 2000/532/EC in conjunction with Directive 75/442/EEC, the assignment of a waste code number must be carried out on a sector-specific basis and in consultation with the regional disposal company.

· **Uncleaned packagings:**

· **Recommendation:** Disposal according to official regulations.

SECTION 14: Transport information

· **14.1 UN-Number**
· **ADR, IMDG, IATA**

UN1950

· **14.2 UN proper shipping name**
· **ADR, IMDG**
· **IATA**

AEROSOLS
AEROSOLS, flammable

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class**
· **Label**

2 5F Gases.
2.1

· **IMDG, IATA**



· **Class**
· **Label**

2.1 Gases.
2.1

· **14.4 Packing group**
· **ADR, IMDG, IATA**

Void

· **14.5 Environmental hazards:**

· **Marine pollutant:**

No

· **14.6 Special precautions for user**

Warning: Gases.

· **Page:**

-

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 69

Revision: 06.12.2022

Trade name tesa Spray Glue extra strong / Spray Glue Mounting

(Contd. of page 8)

· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	Limited quantity regulations concerning ADR and IMDG for packages up to 30 kg (gross weight). ID 8000 Consumer commodity for airtransport of finished goods in packages up to 30 kg possible (gross weight). DOT: ORM-D consumer commodity for road transport inside US
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

* SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 - **Directive 2012/18/EU**
 - **Named dangerous substances - ANNEX I**
 - **Seveso category**
 - **Qualifying quantity (tonnes) for the application of lower-tier requirements**
 - **Qualifying quantity (tonnes) for the application of upper-tier requirements**
 - **National regulations**
 - **Information about limitation of use:**
 - **Decree to be applied in case of technical fault:**
- None of the ingredients is listed.
P3a FLAMMABLE AEROSOLS
- 150 t
- 500 t
- avoids
- Employment restrictions concerning young persons must be observed.
- Critical quantity values according to the regulations on accidents should be adhered to.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.12.2022

Version number 69

Revision: 06.12.2022

Trade name tesa Spray Glue extra strong / Spray Glue Mounting

(Contd. of page 9)

· **Technical instructions (air):**

Class	Share in %
I	0.2
NK	59.6

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This data is based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

· **Department issuing data specification sheet:**

tesa SE, Corporate Regulatory Affairs

· **Contact:**

tesa SE, Corporate Regulatory Affairs, Email: SDS@tesa.com, Tel.: +4940-88899-0

· **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Gas 1A: Flammable gases – Category 1A
- Aerosol 1: Aerosols – Category 1
- Press. Gas (Comp.): Gases under pressure – Compressed gas
- Flam. Liq. 2: Flammable liquids – Category 2
- Acute Tox. 3: Acute toxicity – Category 3
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Repr. 2: Reproductive toxicity – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * **Data compared to the previous version altered.**